

Solis-(100-110)K-5G

Solis Three Phase Inverters



Model:

400V: Solis-100K-5G Solis-110K-5G



360 degree



Efficient

- ▶ 10 MPPTs, max. efficiency 98.7%
- ▶ > 150% DC/AC ratio
- ▶ High power tracking density 90MPPT/MW
- ▶ Compatible with bifacial modules



Safe

- ▶ AFCI protection, proactively reduces fire risk
- ▶ Built-in PID recovery for better module performance (optional)
- ▶ Type I SPD for AC (optional)
- ▶ Overvoltage load reduction and leakage current suppression technology, low failure rate
- ▶ Globally recognised branded componentry for longer life



Smart

- ▶ Night SVG function
- ▶ Intelligent string monitoring. Smart I-V curve scan
- ▶ Remote firmware upgrade with simple operation



Economic

- ▶ Power line communication (PLC) (optional)
- ▶ Support "Y" type connection in DC side
- ▶ Supports aluminium wire access to reduce cost

Datasheet

Model Name	Solis-100K-5G	Solis-110K-5G
Input DC		
Max. input voltage	1100V	
Rated voltage	600V	
Start-up voltage	195V	
MPPT voltage range	180-1000V	
Max. input current	10*26A	
Max. short circuit current	10*40A	
MPPT number/Max. input strings number	10/20	
Output AC		
Rated output power	100kW	110kW
Max. apparent output power	110kVA	121kVA
Max. output power	110kW	121kW
Rated grid voltage	3/N/PE, 220/380V, 230/400V	
Rated grid frequency	50/60Hz	
Rated grid output current	152.0A	167.1A
Max. output current	167.1A	183.8A
Power Factor	>0.99 (0.8 leading - 0.8 lagging)	
THDi	<3%	
Efficiency		
Max. efficiency	98.7%	
EU efficiency	98.3%	
Protection		
DC reverse-polarity protection	Yes	
Short circuit protection	Yes	
Output over current protection	Yes	
Surge protection	DC Type II / AC Type II (AC Type I optional)	
Grid monitoring	Yes	
Anti-islanding protection	Yes	
Strings monitoring	Yes	
I/V Curve scanning	Yes	
Anti-PID function	Optional	
Integrated AFCI (DC arc-fault circuit protection)	Yes	
Integrated DC switch	Yes	
Integrated AC switch	Optional	
General Data		
Dimensions (W*H*D)	1065*567*344.5 mm	
Weight	84kg	
Topology	Transformerless	
Self consumption	<2W (night)	
Operating ambient temperature range	-25 ~ +60°C	
Relative humidity	0-100%	
Ingress protection	IP66	
Cooling concept	Intelligent redundant fan-cooling	
Max. operation altitude	4000m	
Grid connection standard	VDE-AR-N 4105, VDE V 0124, VDE V 0126-1-1, UTE C15-712-1, NRS 097-1-2, G98, G99, EN 50549-1/-2, RD 1699, UNE 206006, UNE 206007-1, IEC 61727, DEWA	
Safety/EMC standard	IEC 62109-1/-2, IEC 62116, EN 61000-6-2/-4	
Features		
DC connection	MC4 connector	
AC connection	OT terminal (max. 185 mm ²)	
Display	LCD	
Communication	RS485, Optional: Wi-Fi, GPRS, PLC	